

destroyit®

BUSINESS SHREDDERS

➔ 2604 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times (cross-cut and SMC models) | wide, 10 1/4" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy "twin drive system" with dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 26 gallon shred volume (approximate)

Dimensions (D x W x H): 18 1/2 x 22 1/2 x 36 1/2 inches, Shipping weight: 123 lbs.



CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator helps prevent paper jams by monitoring capacity levels during operation.

➔ 2604 STRIP-CUT

Strip width	3/16"
Sheet capacity	27-30*
Security level	2
Feed opening	10 1/4"
Max. horsepower	1

➔ 2604 CROSS-CUT

Particle size	3/16" x 1 1/2"
Sheet capacity	20-22*
Security level	3
Feed opening	10 1/4"
Max. horsepower	1

➔ 2604 CROSS-CUT

Particle size	3/32" x 5/8"
Sheet capacity	12-14*
Security level	4
Feed opening	10 1/4"
Max. horsepower	1

➔ 2604 SMC HIGH SECURITY

Particle size	1/32" x 3/16"
Sheet capacity	6-8*
Security level	6
Feed opening	10 1/4"
Max. horsepower	1

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 2/2010.

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com

Dealer: